



FEATURES	BENEFITS
Full three-year sensor warranty	Ensures trouble-free and cost-effective operation when compared to sensors having 6-12 month warranties
Exceptional speed of response	Detects oxygen alarm events in seconds
Extended life oxygen sensor	Eliminates frequent sensor replacement and annoying false low oxygen alarms. Won't fail due to heat fatigue like certain high temperature current limited zirconium oxide sensors.
Economically priced	Saves hundreds of dollars per point
WATCHMAN CIRCUIT™	Alerts users of major status changes in the Series 1000 Oxygen Deficiency Monitor and the environment
CO ₂ resistant sensor	Eliminates sample conditioning and premature sensor failures, while minimizing routine maintenance
Extended life sensor with an expected life of five years	Be aware of high temperature current limited zirconium oxide sensors that can prematurely fail due to heat fatigue.
Open sensor diffuser	No dependence on a sample pump or aspirator

Product Description

The Series 1000 Oxygen Deficiency Monitor is a popular choice of government labs, universities, and industrial facilities to help ensure the quality of breathing air. The Series 1000 Oxygen Deficiency Monitor's primary use is for applications when the possibility exists that breathing air oxygen could be displaced by stored or piped inert gases such as nitrogen, helium, argon, carbon dioxide, etc. resulting in a hazardous condition.

The Series 1000 Oxygen Deficiency Monitor is a microprocessor-controlled instrument with a range of 0-30%. It is powered from a universal 115-230VAC, 50-60Hz. Oxygen values are displayed on an easy-to-read, 10.2 mm (0.4") high, 4-1/2 digit liquid crystal display (LCD). The Series 1000 Oxygen Deficiency Monitor can be equipped with an optional remote sensor enclosure. The oxygen sensor is mounted in a resilient, polycarbonate electronics enclosure. An optional remote sensor enclosure is available for mounting up to several thousand feet from the monitor. In its standard configuration, the electronics enclosure is rated NEMA 1 (IP 30).

The eloquence of the Series 1000 Oxygen Deficiency Monitor is its ease of use. The electronics and optional remote sensor enclosures are equipped with mounting holes molded into each of the four corners for quick and easy installation. The front panel of the Series 1000 Oxygen Deficiency Monitor contains five switches that provide access to the instrument's settings. The Series 1000 Oxygen Deficiency Monitor is equipped with three oxygen alarm relays and one status alarm relay.

All four relays are Form C (SPDT) types rated at 10 amps at 110/220VAC and 30VDC. The relays are user configurable for fail-safe operation. In addition to the four alarm contacts, the Series 1000 Oxygen Deficiency Monitor has a built-in audible alarm and three red LEDs for visual indication of an oxygen alarm condition. The audible alarm may be manually canceled at any time. If the audible alarm is canceled and the alarm event continues, indications of this condition will still be available through the front panel LEDs and the relay contact(s).

The Series 1000 Oxygen Deficiency Monitor comes equipped with two standard analog outputs: 4-20mADC and 0-2VDC for use with recorders, dataloggers, etc. For enhanced communications, the Series 1000 Oxygen Deficiency Monitor comes configured with standard RS-232C or optional RS-485 serial communications. For multiple point installations, the RS-485 format provides the capability to send digital signals over greater distances and to control each monitor using the same communications channel.

The sensor in the Series 1000 Oxygen Deficiency Monitor has an open diffuser design and does not require a sample pump or aspiration system. Since the extended life sensor is sealed, it does not require an initial charge of electrolyte, or a periodic "topping off" due to evaporation, as do other types of oxygen sensors. Users do not have to handle caustic electrolyte (a hazardous substance).

Specifications		Audible Alarm:	Internal buzzer
PERFORMANCE		Audible Alarm Cancel:	Front panel
Measurement Range:	0-30% Oxygen	Instrument Status Alarm Relay:	Front panel 1 SPDT Form C rated identical to above
Accuracy:	±1% of full scale	CONSTRUCTION	
Response Time:	90% of full scale response in less than 12 seconds	Electronics Control Unit:	Light gray polycarbonate with a hinged clear front cover. Rated NEMA 1 (IP 30).
Sensor Type:	Extended Life Ambient Temperature Electrochemical Type	Electronics Control Unit Dimension:	9.44 in. (239.8 mm) length 6.29 in. (159.8 mm) width 3.54 in. (89.9 mm) height <small>Note: All dimensions are without optional equipment</small>
Temperature & Pressure Compensation:	Standard	Sensor Mounting:	Either in the electronics enclosure or remotely
Operating Temperature:	5° to 40° C (40° to 104°F)	Sensor Inputs:	One
Product Warranty:	Three years sensor and electronics	Optional Remote Enclosure Dimensions:	Light gray polycarbonate rated NEMA Sensor Enclosure: 1 (IP 30) 4.72 in. (119.9 mm) length 3.14 in. (79.8 mm) width 3.34 in. (84.8 mm) height <small>Note: All dimensions are without optional equipment</small>
ELECTRICAL		Weight (Control Unit):	4.08 kg. (9 lbs.)
Display:	10.2 mm (0.4") high, 4-1/2 digit liquid crystal display. Resolution 0.1%.	(Remote Sensor):	<0.45 kg (<1 lb.)
Input Power:	Universal 115-230VAC, 50-60Hz		
Standard Outputs:	4-20mADC and 0-2VDC		
Digital Outputs:	Standard RS-232C or optional RS-485		
Oxygen Alarm Relays:	Three (3) SPDT Form C contacts rated 10 A @30VDC/110/220VAC. Alarm clearing is user selectable for either manual or automatic.		



THE AMERICAS

4140 World Houston Pkwy,
Suite 180, Houston, TX 77032
Tel: +1 631 618 9826
+1 401 333 8580
+1 800 262 5977
Email: c.service@cosaxentaur.com
Web: aoi-corp.com

EMEA

ATRICOM Lyoner StraÙe 15
60528 Frankfurt
Germany
Tel: +49 69 20436910

APAC

Wujiang Economic and Technology
Development Zone
No. 258 Yi He Road
215200 Suzhou, Jiangsu Province
China
Tel: +86 21 5068 8521

