

SERIES 1300 OXYGEN DEFICIENCY MONITOR



SYSTEM DESCRIPTION

The Series 1300 Oxygen Deficiency Monitor is a digitally controlled instrument with a measuring range of 0-30%. Oxygen values are displayed to the nearest tenth of a percent on a high contrast front panel liquid crystal display (LCD). The monitor is housed in a resilient polycarbonate, wall mountable general purpose enclosure. Standard input power to the Series 1300 is 90-264 VAC, 47-63 Hz. and 18-36 VDC powered systems are available. Battery backup power is an option. The eloquence of the Series 1300 is its simple operation, as well as its ease of expandability. Included are four individually adjustable Form C alarm relays. The Series 1300 can be programmed to provide a maximum of nine individual alarm events and can be expanded to support up to a maximum of 8 remote optional horn and strobe annunciators with a single monitor. Two scaleable analog outputs are standard, as is RS-232 serial communications. Each Series 1300 includes an internally mounted audible alarm as well as visual alarm indicators.

ENHANCED ELECTROLYTE SYSTEM (EES)

The Series 1300 Oxygen Deficiency Monitor can be equipped with a local oxygen sensor and/or up to two remote sensors. The sensors featured in the Series 1300 are extended life electrochemical oxygen sensors designed with a proprietary Enhanced Electrolyte System (EES™) that extends the life expectancy of the sensor to years instead of approximately 12 months typical of most "fuel cell type" sensors. The oxygen sensors are designed with open diffusers eliminating the need to use sample pumps. The sensors are backed with a **full three (3) year warranty**. Users can expect sensor life well beyond 5 years, helping to ensure reliable and trouble free performance.

AWAY WITH FREQUENT FALSE LOW ALARMS

A common problem caused by fuel cell type sensors is the tendency of the monitor to produce false low oxygen alarms due to the rapid depletion of the sensor's anode. As the sensor deteriorates, its electrical output drops simulating a low oxygen signal often resulting in false low oxygen alarms. When false low oxygen alarms happen on a repeated basis, a potentially dangerous condition is created. Personnel may choose to ignore

the alarms believing "its just another false alarm" even if it is an actual low oxygen event. The Series 1300's oxygen sensor with EES™ greatly enhances the stability of the oxygen measurement helping to eliminate these annoying and troublesome problems.

ADVANCED DIGITAL INTERFACE (ADI)

Alpha Omega Instruments Advanced Digital Interface (ADI) provides the ability to easily and quickly expand the capabilities of the Series 1300. With ADI, the Series 1300 is easily field expandable to operate with a maximum of three oxygen sensors and eight optional horn and strobe annunciators. ADI automatically detects the addition of sensors and/or horn and strobes for quick and effortless expansion of the Series 1300. ADI also detects if a sensor(s) is enabled but not connected, ensuring the integrity of the areas being monitored.

BUILT-IN DATA LOGGER-STANDARD

Among the many standard features of the Series 1300 Oxygen Deficiency Monitor is the built-in data logger providing the capability to store time-stamped oxygen data. Users can download oxygen data via RS-232 for subsequent use with conventional spreadsheet programs. Real-time or historical oxygen data can be displayed as well as documented. This is particularly useful when attempting to meet municipal, state, and federal regulatory requirements, or for mandated verification at the plant level.

LET'S CLEAR UP THE FUZZY CLAIMS

A number of manufacturers of oxygen monitors using high temperature zirconium oxide sensors (CLO₂) claim the monitors operate for over 10 years without requiring calibration. However, the instruction manuals often tell a different tale. Wording such as, "over time, oxygen readings may decrease in value and adjustments to the oxygen readings must be made" (**also known as calibration**) contradict the marketing hype. Individuals experienced with safety monitors recognize that periodic instrument checks are essential to help ensure the safety of personnel.

COMPARISON OF OXYGEN MONITORS

FEATURES	SERIES 1300 OXYGEN MONITOR	FUEL CELL OXYGEN MONITORS	HIGH TEMPERATURE ZIRCONIUM OXIDE (CLO ₂) MONITORS
3 Year Warranty on Both Electronics and Sensor.	YES	NO	NO
Accepts up to a maximum of 3 Oxygen Sensors with a single Electronic Control Readout.	YES	NO	NO
Built-in Data Logger Standard.	YES	NO	LIMITED AVAILABILITY
Easy Field Replacement of Sensor.	YES	YES	NO- When the sensor fails from high temperature fatigue (@450C) both sensor and electronics often need replacement representing a significant expense.
Built-in Four Alarm Relay Contacts Standard.	YES	NO	NO
<u>In</u> sensitive to Changes in Ambient Air Flow (HVAC/ Air Handling Systems).	YES	YES	NO- Changes in airflow may cool the high temperature sensor producing erroneous oxygen readings.
Protection From Frequent False Low Oxygen Alarms.	YES	NO	YES
Quick Start-up	YES	YES	NO- Typically takes 30-60 minutes to "warm up".

OVERALL PERFORMANCE

Measurement Range:	0 to 30% Oxygen
Accuracy:	± 1 % of full scale
Response Time:	90% of full scale response in <20 seconds
Sensor Type:	Extended Life Electrochemical Oxygen Sensor
Temperature Compensation:	Standard
Operating Temperature:	50° to 104° F (10° to 40°C) /90% max humidity (non-condensing)
Product Warranty:	3 years sensor 3 years electronics
Calibration:	Ambient air or calibration gas

ELECTRICAL

Display:	4 Line by 20 Character LCD
Input Power:	Universal 90 to 264 VAC, 47 to 63 Hz standard. Optional 18-36 VDC available.
Standard Outputs:	Two 0-20 mADC or 4-20 mADC, user configurable
Serial Communication:	RS-232 Standard

Oxygen Alarm Relays:

Four (4) SPDT Form C contacts rated 10A (250 VAC) 5A (100 VDC). Alarms may be cleared manually or auto-matically (latching), by user selection. Individually configurable to be set as high or low alarms for any sensor.

Audible Alarm:

Internal audible alarm rated at 85 decibels (nominal) with specific alarm canceling accessible via menu

Data Logger:

1 to 60 second time interval. Selectable sensors. Selectable Time stamp. Output in character separated values (CSV).

MECHANICAL

Electronics Control Unit:

Light gray polycarbonate, equivalent to NEMA 1 (IP 30). Wall mountable.

Electronics Control Unit Dimensions:

Depth: 3.5 in (90.1 mm)
Width: 6.3 in (159.2 mm)
Height: 10.8 in (274.9 mm)

Sensor Mounting:

Either within electronics enclosure or with remote sensor enclosure

Sensor Inputs:

Up to a maximum of three (3)

Optional Remote Sensor Enclosure:

Light gray polycarbonate, equivalent to NEMA 1 (IP 30)

Optional Remote Sensor Enclosure Dimensions:

Depth: 3.5 in (90.1 mm)
Width: 6.7 in (170.2 mm)
Height: 6.1 in (154.9 mm)

Weight: Control Electronics Remote Sensor

3.2 lbs. (1.45 kg)
0.8 lbs. (0.36 kg)

THE AMERICAS

EMEA

APAC