



Product shown with optional flow meter and pressure regulator

FEATURES	BENEFITS
<b>State-of-the-Art Sensor Technology</b>	<b>High Precision Measurements</b>
<b>Light Weight/Compact Design</b>	<b>Easy to Carry and Transport</b>
<b>Rapid Speed of Response</b>	<b>Senses Oxygen Changes in Seconds</b>
<b>Built-in NICAD Batteries</b>	<b>Provides Hours of Continuous Operation</b>
<b>Uses Standard NICAD's</b>	<b>Replacement Batteries Found World-wide</b>
<b>Minimum Maintenance</b>	<b>Low Cost of Ownership</b>
<b>Factory Calibration</b>	<b>Factory calibration and certificate included at no additional charge</b>

## Product Description

The Series 3520 Trace Oxygen Analyzer is a portable, battery operated trace oxygen analyzer designed for industrial and commercial applications where accurate and reliable spot trace oxygen measurements are needed. The Series 3520 Portable Oxygen Analyzer features Alpha Omega Instruments long life ambient temperature electrochemical sensor. The enclosure is made from durable polycarbonate and is rated NEMA 1 for general purpose service. The instrument is powered from rechargeable NICAD batteries that are mounted internal to the analyzer. Recharging of the batteries is accomplished using a built-in battery charger with a universal AC adapter. Single measurement ranges are available from 0-10 PPM to 0-20,000 PPM with values displayed on a front panel liquid crystal display (LCD). Options include pressure regulators, flow meters, in-line filters, sample pumps, and block & bleed bypass sampling systems.

### High Performance Trace Oxygen Sensor

The Series 3520 Trace Oxygen Analyzer features Alpha Omega Instrument's long-life ambient temperature electrochemical sensor that has a functional life of up to three times that of most "fuel cell" type sensors. The enhanced mechanical design of the sensor ensures longer life, and virtually eliminates

leakage of caustic electrolyte, a nagging (and expensive) problem associated with sensors that require periodic electrolyte maintenance. And, because the sensor is sealed, it is not position sensitive. In addition, unlike some electrochemical sensors, Alpha Omega Instruments readings from the Series 3520 do not require manual adjustment based on changes in the molecular weights of the sample gas i.e. helium, hydrogen, etc. a major advantage for continuous measuring applications. The output from the sensor is both linear and temperature compensated to provide optimum performance.

### Now Featured a CO<sub>2</sub> Resistant Sensor

A nemesis for many conventional "fuel cell" type trace oxygen sensors are their inability to measure oxygen in gases containing carbon dioxide. Carbon dioxide reacts with potassium hydroxide electrolyte to form carbonic acid and in short time destroys the sensor. Not anymore. Alpha Omega Instruments offers an optional CO<sub>2</sub> tolerant trace oxygen sensor with proprietary electrolyte. The CO<sub>2</sub> tolerant sensor is capable of providing accurate oxygen readings in gases containing up to 100% CO<sub>2</sub> without shortening the life of the sensor.

#### Specifications

##### PERFORMANCE

Measurement Ranges (parts per million)

0-10, 0-50, 0-100, 0-200, 0-500, 0-1,000, 0-5,000, 0-10,000, and 0-20,000

Accuracy<sup>1</sup>: ± 1% of full scale

Linearity: ± 1% of full scale

Response Time: 90% of full scale response in <10 seconds (typical). The response time for ranges of 0-50 PPM or less depend to a great extent on the design of the sample delivery system including the materials used.

Sensor Type: Long-life Ambient Temperature Electro-chemical Sensor (Optional CO<sub>2</sub> Resistant Sensor Available)

Temperature Compensation: Standard

Operating Temperature Range: 40° to 104° F (5° to 40° C)

Warranty: 2 years electronics/1 year sensor

##### ELECTRICAL

Display: 3-1/2 digit liquid crystal display (4-1/2 digit for the 0-5,000, 0-10,000, and 0-20,000 ppm range instruments)

Input Power: Powered from eight AA Rechargeable NICAD batteries with built-in universal AC battery charger

Analog Output: No analog output

##### SAMPLE GAS CHARACTERISTICS

Sample Flow Rate: 1.0 to 2.0 SCFH (0.5 to 1.0 liters/min)

Sample Gas Temperature: 40° to 104° F (5° to 40° C)

Sample Gas Pressure Limits: 0.1 to 1.5 psig (0.007 to 0.1 kg/cm<sup>2</sup>)

Entrained Solids: <3 mg/ft<sup>3</sup>: no in-line filter required  
>3 mg/ft<sup>3</sup>: in-line filter is required

Hydrocarbon Mist: <0.7 mg/ft<sup>3</sup>: no in-line filter required  
>0.7 mg/ft<sup>3</sup>: in-line filter is required

##### CONSTRUCTION

Enclosure: Polycarbonate rated NEMA 1

Dimensions: 6.5 inches (165.1 mm) height

6.5 inches (165.1 mm) width

7.8 inches (196.9 mm) height

Note: All dimensions are without optional equipment

Gas Connections: 1/4" stainless steel compression fittings

<sup>1</sup> Stated at constant temperature and constant pressure



#### THE AMERICAS

4140 World Houston Pkwy,  
Suite 180, Houston, TX 77032

Tel: +1 631 618 9826

+1 401 333 8580

+1 800 262 5977

Email: c.service@cosaxentaur.com

Web: aoi-corp.com

#### EMEA

ATRICOM Lyoner Straße 15  
60528 Frankfurt

Germany

Tel: +49 69 20436910

#### APAC

Wujiang Economic and Technology  
Development Zone

No. 258 Yi He Road

215200 Suzhou, Jiangsu Province

China

Tel: +86 21 5068 8521

